

## Silt Fence 3606-FLA48-7

### Product # 76187

Hanes Geo Components preassembled Silt Fence 3606-FLA48-7 is a preassembled silt fence with TerraTex SF-90 woven geotextile, stapled to hardwood stakes, 6 feet on center.

#### Assembled Fence Characteristics

Silt Fence Geotextile	<b>TerraTex SF-90</b>
Geotextile Height / Length	<b>36 in (0.914 m) x 100 ft (30.48 m)</b>
Post Spacing	<b>6 feet (1.83 m)</b>
Post Height	<b>48 inches (1.22 m)</b>
Post Composition	<b>Common Hardwood</b>
Post Size	<b>1.25 in x 1.25 in</b>
Fence Assembly	<b>5 -16g Galvanized Staples/post</b>
Lathe / Support netting or wire	<b>None</b>

The TerraTex SF-90 is made up of polypropylene filaments. These filaments are woven to form a stable and durable network such that the filaments retain their relative position. It is non-biodegradable and resistant to most soil chemicals, acids, and alkali with a pH range of 3 to 12. TerraTex SF-90 is manufactured to meet or exceed AASHTO M288 supported silt fence fabric requirements and the following minimum average roll values:

#### Silt Fence Geotextile Properties

<u>Property</u>	<u>Test Method</u>	Minimum Average Roll Value <u>English</u>	Minimum Average Roll Value <u>Metric</u>
Grab Tensile MD	ASTM D-4632	100 lbs	445 N
Elongation MD	ASTM D-4632	15 %	15 %
Grab Tensile XMD	ASTM D-4632	100 lbs	445 N
Elongation XMD	ASTM D-4632	15 %	15 %
UV Resistance	ASTM D-4355	80% @ 500 hr	80% @ 500 hr
AOS*	ASTM D-4751	30 US Sieve	0.60 mm
Permittivity	ASTM D-4491	0.10 sec <sup>-1</sup>	0.10 sec <sup>-1</sup>
Flow Rate	ASTM D-4491	8 gal/min/ft <sup>2</sup>	325.6 L/min/m <sup>2</sup>

\* Maximum Average Roll Value

5/2014